

REPUBLIC OF KENYA

REQUEST FOR QUOTATION

To:

Seller's name and address

.....
.....
.....
.....

Quotation No NYCG/Q278/2016-2017

Date...10/05/2017.....

From:

Buyer's Designation and Address

County Government of Nyamira
Supply Chain Management Office,
P.O. Box 434-40500 NYAMIRA

You are invited to submit quotation on materials listed below:

Notes:

costs for

- (a) THIS IS NOT AN ORDER. Read the conditions and instructions on reverse before quoting.
- (b) This quotation should be submitted in a plain wax sealed envelope marked "Quotation No. for supply of **.PLAYFIELDS UPGRADING** and be addressed to reach the buyer or placed in the Quotation/Tender box not later than 9.30 a.m. on**16/05/2017**.....

- (c) Your Quotation should indicate final unit price which includes all delivery, discounts duty and sales tax
- (d) Return the original copy and retain the duplicate for your record.
- (e) Attach proof of KRA registration VAT/PIN certificates
- (f) Attach Business registration/Incorporation of company certificate.
- (g) Fill the attached S33 form.
- (h) Tax Compliance certificate copy
- (i) Attach prove of past experience of similar services/works

Code No.	Item Description	Quoted Amount	Remarks
	Please quote as per the attached BQ for Bosamaro Ward - Kuura Primary School		

FOR OFFICIAL USE ONLY

Opened by: (1) Designation Signature

(2) Designation Signature

(3) Designation Signature

(4) Designation Signature

CONDITIONS

1. The General Conditions of Contract with Government of Kenya apply to this transaction. This form properly submitted constitutes the entire agreement.
2. The offer shall remain for 30 days from the closing date unless otherwise stipulated by the seller.
3. The buyer shall not be bound to accept the lowest or any other offer, and reserves the right to accept any offer in part unless the contract is stipulated by the seller.
4. Samples of offers when required will be provided free, and if not destroyed during tests will, upon request, be returned at the seller's expenses.

INSTRUCTIONS

1. All entries must be typed or written in ink. Mistakes must not be erased but should be crossed out and corrections be made and initiated by the person signing the quotation.
2. Quote on each item separately, and in units as specified.
3. This form must be signed by a competent person and preferably it should be also rubber stamped.
4. Each quotation should be submitted separately in a sealed envelope with the quotation Number endorsed on the outside. Descriptive literature or samples of items offered may be forwarded with the quotation.
5. If you do not wish to quote, please endorse the reason on this form and return it, otherwise your name may be deleted from the buyer's mailing list for the items listed hereon.

PLAY FIELDS FOR UPGRADING IN COUNTY WARDS

REPUBLIC OF KENYA



DEPARTMENT OF TRANSPORT, ROADS AND PUBLIC WORKS

**PROPOSED FENCING, GATE, CONSTRUCTION OF
SHED, DRAINAGE AND GOAL POSTS**

AT

KUURA PRIMARY SCHOOL(BOSAMARO WARD)

PREPARED BY:

COUNTY WORKS OFFICE,

P.O BOX 27-40500, NYAMIRA.

	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
	<u>DRAINAGE AND GOAL POSTS</u>				
	<u>Storm water drainage</u>				
A	Excavate for trenches, embankment to trenches and do batching to specific areas	515	L.M		
	<u>Goal posts (Football, Netball and Volleyball)</u>				
B	Fabricate,deliver and install international fibre standard measurement or other approved alternative (measurement to be determined on site)	10	No		
	TOTAL FOR DRAINAGE AND LEVELLING CARRIED TO GRAND SUMMARY				

GRAND SUMMARY

ITEM	DESCRIPTION	PAGE	OFFICIAL USE	TENDERER'S USE
	-		Kshs	Kshs
1	FENCING AND GATE	PG1		
2	SHED	PG 4		
3	DRAINAGE AND GOAL POSTS	PG 1		
4	PROVISIONAL SUMS	PG 1		
5	SUB-TOTAL			
6	ADD 16% V.A.T			
	TOTAL TENDER AMOUNT CARRIED TO FORM OF TENDER.....			

NAME OF TENDERER.....

ADDRESS.....

DATE.....

NAME OF WITNESS.....

ADDRESS.....

SIGNATURE.....

DATE.....

ITEM	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
	SHED				
	ELEMENT NO 01				
	SUBSTRUCTURES (ALL PROVISIONAL)				
	Excavation and Earthworks				
A	Excavate oversite average 200mm deep to remove vegetable soil load up wheel and deposit about 100metres away and later spread and level on site where directed area measuring 3m by 10m	1	Item		
B	Excavate for strip foundation starting from reduced level not exceeding 1.50metres deep commencing from reduced level	32	C.M		
	Hardcore				
C	250mm Thick layer of imported Hardcore filling including levelling and consolidating 150mm layers	30	SM		
	Blinding				
D	50mm Thick quarry dust blinding to the surface of hardcore; rolled smooth to receive polythene sheeting	30	S.M		
	Insecticide treatment				
E	Treat surface of harcore with "Premise 2000CC" or other equal and approved anti- termite insecticide applied strictly in accordance with manufactures printed instructions	30	S.M		
	Damp proof membrane				
F	500mm Gauge polythene or other equal and approved plastic sheet damp proof membrane laid over blinding (measured nett- allow for laps)	30	S.M		

	Vibrated reinforced concrete (1:2:4) class 20/20				
	aggregates as described in:-				
G	Strip foundation	2	C.M		
H	150mm Thick surface bed	30	S.M		
	Fabric; B.S 4483				
I	Fabric mesh reinforcement to B.S 4483 Ref: A98				
	including laps tying wire and spacer blocks complete (measured nett- for laps)	30	S.M		
J	Edge of floor slab 75-150mm high	26	L.M		
K	150mm thick burnt clay bricks foundation walling and jointing in cement sand (1:3) mortar and reinforced with and including 20swg x25mm wide hoop iron in every alternate course	23	S.M		
	TOTAL FOR SUBSTRUCTURES CARRIED TO SUMMARY				
ITEM	DESCRIRPTION	QTY	UNIT	RATE	AMOUNT
	SUPERSTRUCTURAL CONSTRUCTION				
A	75mm/3mm thick blade pipes steel stanchions complete with concrete and anchorage	20	L.M		
B	50x 50x 3mm SHS rafters	65	LM		
C	50x 50x 2mm SHS steel purlins bolted onto rafters with appropriate cleats	28	L.M		
D	Gauge 30 box profile iron sheet covering complete with hold down bolts and rubber washers	28	S.M		
	concrete bench				
E.	Seats. Reinforced concrete seats complete with reinforcements and formwork to engineers specifications	12	S.M		

ITEM	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
	<u>FENCING AND GATE</u>				
	<u>Chain Link & STRAINING WIRE</u>				
A	2400mm High 14 Gauge chainlink fence fixed on posts (m.s) at 2000mm centres complete with and including Eight strands straining wire to approval	456	L.M		
B	Cedar posts of 2400mm high including 300x300 x 600mm deep plain concrete class 25 including all necessary excavations	228	NO		
C	Extra Over cedar posts for straining posts with one strut	32	NO		
D	Ditto with two struts	16	NO		
	<u>Gate Post</u>				
E	300 x300 x2400mm High reinforced concrete class 25 gate post, 350x 350x 75mm saddle-back capping at top and four 12mm x100mm long mild steel hooks and three gate hinges (m.s) cast into post which is fair face finished and emulsion plastic painting and backfill by compacting in layers of 150mm i.e Column base -1200 x 12000mm (post main- column 300x 300x 2400mm high)	3	NO		
	<u>GATE</u>				
	<u>Mild Steel primed Red oxide before fixing and painted afterwards three coats gloss paint</u>				
F	Double leaf gate overall size 5000x 2100mm high each leaf tapering and rising by 1m as they meet with top spikes at 150mm centre in two equal leaves; each leaf comprising 75 x25 x3 mm R.H.S framed two 75x 25 x3mm middle rails and 25x 25 x3mm R.H.S vertical members welded to rails and frame at 75mm centres and plugged top and bottom each leaf hang on gate posts (m.s) on three purpose made heavy duty hinges with brass bush set in and proved with 2NO. 750mm long drop barrel bolt and brass castor including 1200mm diameter 16Gauge mild steel sheet on both sides on each leaf	1	NO		
G	Single leaf pedestrain gate overall 1200 x2100mm high comprising 75 x25 x3mm R.H.S framing all round; two 75x 25 x3mm middle rails and 25x 25 x3mm R.H.S vertical members welded to rails and frame at 75mm centres; the whole hung on 3NO. purposes made heavy duty hinges with brass bush and provided with locking devices and one 200mm long drop bolt	1	NO		
FOR FENCING AND GATE CARRIED TO GRAND SUMMARY					